


LEAK DETECTORS

Tubing & Clamps

PVC TUBING

SPECIFICATIONS FOR PVC TUBING	
Hardness, Shore A ±5	73
Specific Gravity	1.22
Tensile Strength, PSI	2100
Elongation at Break, %	270
Brittle Temperature	-23°F
Max. Operating Temp.	150°F



Spiral steel reinforcement incorporated within wall.

DUNIWAY PART #	I.D.	HOSE O.D.	CLAMP SIZE	PRICE/FT
PVC-5/8	5/8"	.906"	#16	\$4.00
PVC-3/4	3/4"	1.024"	#16	5.00
PVC-1	1"	1.319"	#20	6.00
PVC-1 1/4	1 1/4"	1.634"	#24	8.00
PVC-1 1/2	1 1/2"	1.909"	#28	11.00
PVC-2	2"	2"	#36	14.00

CLAMPS

FOR PVC & GUM RUBBER

DUNIWAY PART #	CLAMP SIZE	PRICE
CLP-5/8	#16	\$2.50
CLP-3/4	#20	2.50
CLP-13/16	#24	2.50
CLP-1	#28	2.50
CLP-1-1/4	#32	2.50
CLP-1-1/2	#36	2.50
CLP-1-5/8	#44	3.50
CLP-2	#44	3.50

GUM RUBBER TUBING

SPECIFICATIONS FOR GUM RUBBER TUBING	
Hardness, Shore A ±5	45
Specific Gravity	1.08
Tensile Strength, PSI	3000
Average Elongation, %	600
Brittle Temperature	-40°F
Max. Operating Temp.	180°F



Gum Rubber Tubing

Sections longer than 4-8" must be supported internally.

DUNIWAY PART #	WALL	I.D.	CLAMP SIZE	PRICE/FT
VH-5/8	3/8"	5/8"	#16	\$7.00
VH-3/4	3/8"	3/4"	#20	8.50
VH-13/16	3/8"	13/16"	#24	8.50
VH-1	1/2"	1"	#28	16.00
VH-1-1/4	1/2"	1 1/4"	#32	18.00
VH-1-1/2	1/2"	1 1/2"	#36	18.00
VH-1-5/8	11/16"	1 5/8"	#44	25.00
VH-2	1/2"	2"	#44	25.00



Liner type hose clamps prevent hose from extruding through thread holes in the band.