



## HAZARDOUS MATERIAL NOTIFICATION

48501 Milmont Drive, Fremont, CA 94538  
Phone: 650-969-8811 | Fax: 650-965-0764

Duniway CSR Contact Name: \_\_\_\_\_

**INSTRUCTIONS:** 1. Save this form to your computer 2. Open the form in Adobe Reader 3. Completely fill out and sign the form 4. Return the completed form to your Duniway CSR Contact or email to info@Duniway.com

**From:** Company: \_\_\_\_\_

Address: \_\_\_\_\_

Attn: \_\_\_\_\_

**Manufacturer:** \_\_\_\_\_ **Model Number:** \_\_\_\_\_ **Serial Number:** \_\_\_\_\_ **Description:** \_\_\_\_\_ **Oil Type:** (if applicable)

1) \_\_\_\_\_ 2) \_\_\_\_\_ 3) \_\_\_\_\_ 4) \_\_\_\_\_  
5) \_\_\_\_\_ 6) \_\_\_\_\_ 7) \_\_\_\_\_ 8) \_\_\_\_\_  
9) \_\_\_\_\_ 10) \_\_\_\_\_

The equipment above was used for the following purpose(s):  
\_\_\_\_\_  
\_\_\_\_\_

**KNOWN MATERIALS IN CONTACT WITH THE EQUIPMENT ABOVE ARE:** (place an "X" in any applicable categories)

Potentially Hazardous  Biologically Hazardous  Non-Hazardous  
 Unknown if Hazardous  Toxic  Corrosive  Explosive

**- PLEASE BE ADVISED: DUNIWAY STOCKROOM CORP IS NOT EQUIPPED TO HANDLE RADIOACTIVE MATERIAL -**

List the gases, chemicals, and/or materials to which the equipment above was exposed during its use:  
\_\_\_\_\_  
\_\_\_\_\_

| All oil sealed pumps must be drained and <b>flushed*</b> prior to shipping to Duniway |          |       |       |       |
|---|----------|-------|-------|-------|
| Non-flushed pumps subject to the charges listed: (based on the pump's oil capacity)   | Gallons: | 0 - 1 | 1 - 4 | 4 +   |
|   | Charges: | \$100 | \$250 | \$500 |

**CONTACT INFORMATION FOR QUESTIONS REGARDING LAST USE OF THE EQUIPMENT ABOVE:**

Name: \_\_\_\_\_ Phone: \_\_\_\_\_ Email: \_\_\_\_\_

This form completed by: \_\_\_\_\_ Print: \_\_\_\_\_

Signature: (required) \_\_\_\_\_ Date: \_\_\_\_\_

**THANK YOU FOR YOUR HELP IN SAFEGUARDING OUR EMPLOYEES AND THE ENVIRONMENT**

\*flushed refers to "draining the oil from your pump & refilling the pump w/the most cost efficient vacuum pump oil available to run the pump blanked off for a few minutes & then fully drain your pump again." If upon initial draining your oil is clean, then the pump only needs to be drained, not flushed. Please inquire on specific instructions for PFPE pumps.